**Languages:**

- **English**
- Español

## Table of Contents

Languages: 1
ADDREDIT 2

## ADDREDIT

NAME

AddrEdit -- Fill in the fields of the current address book entry. (V2.0)

TEMPLATE

ALIAS,NAME,EMAIL,PGP,HOMEPAGE,STREET,CITY,COUNTRY,PHONE,COMMENT, BIRTHDATE/N,IMAGE,MEMBER/M,ADD/S

FUNCTION

Edits the fields of the current address book entry.

INPUTS

`ALIAS` - alias for the entry (upto 29 chars)
`NAME` - real name for the entry (upto 39 chars)
`EMAIL` - email address for the entry
`PGP` - PGP ID for the entry (person only)
`HOMEPAGE` - homepage for the entry (person only) (upto 231 chars)
`STREET` - snail mail address of the entry (person only) (upto 79 chars)
`CITY` - city for the entry (person only) (upto 79 chars)
`COUNTRY` - country for the entry (person only) (upto 79 chars)
`PHONE` - phone # for the entry (person only) (upto 79 chars)
`COMMENT` - comment for the entry (up to 79 chars)
`BIRTHDATE/N` - birthdate for a person in DDMMYYYY format, e.g. 13091969
`IMAGE` - image filename for the entry (person only)
`MEMBER/M` - use the argument(s) to edit a member list
`ADD/S` - combined with 'member', adds new members to a distribution list, instead of replacing the old member info

RETURNS

`RC` is set 10 if no entry is currently selected in the address book.

NOTES

Arguments longer than the available space are simply truncated.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Select an entry */
ADDRGOTO YAM_ml

/* Edit this entry */
'ADDREDIT EMAIL "yam@freelists.org" COMMENT "The place to be"'

/* Select a distribution list */
ADDRGOTO blacklisted

/* Reset the list */
ADDREDIT MEMBER 'bill'

/* Add a couple of members */
ADDREDIT MEMBER 'jobs@example.com' MEMBER 'smith@example.net' ADD
```

BUGS

Even if a group or person is selected, `MEMBER [ADD]` will return success (0).

Entering nonsense data as birth date or editing a distribution list would throw Enforcer hits; this was fixed in V2.4.

SEE ALSO